REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	YCH 12/15/07'	~	

R/A type
WITH EAR TYPE



V/T type



R/A type
WITH POST TYPE



R/A type
W/O EAR AND POST TYPE



NOTES:

1. MAIN SPECIFICATIONS
   - . Housing material: NYLON 66
   - . Rated voltage: 250V
   - . Rated current: 3A
   - . Contact resistance: ≤100mΩ
   - . Insulation resistance: ≥1000MΩ
   - . Withstanding voltage: 500V,AC 1 minute
   - . Temperature range: −45 ~ +110°C
   - . Recommend PC board thickness:1.6mm
2. PRODUCT NUMBER CODE:

DS1073−01− X X X X X

- Contact Plating
  - 6: Tin
  - 8: Full gold flash
- Housing Color
  - T: Transparent
- Mounting type
  - V: V/T type
  - R1: R/A with ear type
  - R2: R/A with post type
  - R3: R/A W/o ear and W/o post type
- Connector type
  - M: Male
- No.of contact
  - 2*2−2*10

GENERAL TOLERANCE	ANGLE TOLERANCE
X. ±0.60	X. ±5°
.X ±0.38	.X ±3°
.XX ±0.25	.XX ±2°

DRAWING TYPE	CUSTOMRE		
SCALE	1:1	SHEET	1 OF 1
DRAWING NO.	C−DS1073−01−XXXXX−A		

PROJECTION		TITLE	ATX CONNECTOR PITCH 4.2mm DIP & R/A type
UNITS	mm		
SHEET SIZE	A4	SERIES	DS1073−01 SERIES

晨翔电子有限公司
CONNFLY ELECTRONIC CO. LTD

CONNFLY
Tel:86−574−63508787
Fax:86−574−63510817
E-mail:sale@zhenqin.com.cn
Http://www.connfly.com
Add:East Industry Zone, Jiang Yan Town Cixi Ningbo China
P.C315.55