





Hubei Kento Electronic Co., Ltd

Specification for LED Product

5AYY3UC09

Package Dimensions(mm)




Notes:

All dimension units are millimeters.

All dimension tolerance is ± 0.2 mm unless otherwise noted.

An epoxy meniscus may extend about 1.5mm down the leads.

Burr around bottom of epoxy may be 0.5mm max.



Synopsis:

5mm Round Type

Water Clear Lens

Yellow LED Lamp



Hubei Kento Electronic Co., Ltd

Typ 5AY3UC09

Typical Electrical & Optical Characteristics (Ta = 25°)

ITEMS	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT
Forward Voltage	VF	IF = 20mA	1.4	1.9	2.4	V
Reverse Current	IR	VR = 5V	---	---	1.1	µA
Dominant Wavelength	λD	IF = 20mA	586	---	590	nm
Luminous Intensity	IV	IF = 20mA	2338	2685	3395	mcd
50% Power Viewing Angle	20½	IF = 20mA	---	13	---	deg

Absolute Maximum Ratings at (Ta = 25°C)

ITEMS	SYMBOL	ABSOLUTE MAXIMUM RATING	UNIT
Forward Current	IF	50	mA
Peak Forward Current	IFP	220	mA
Continuous Forward Current	IL	20	mA
Reverse Voltage	VR	5	V
Power Dissipation	PD	95	mW
Operation Temperature	Topr	-40 ~ +80	°C
Storage Temperature	Tstg	-40 ~ +80	°C
Lead Soldering Temperature	Tsol	Max.260°C for 5 sec Max.	

IFP Conditions Pulse Width 10msec duty 1/10


Tsol Conditions 4mm from the base of the epoxy bulb



Hubei Kento Electronic Co., Ltd

5AY3UC09

Spatial Distribution



Reliability Performance


Test Classification	Test Item	Test Conditions	Test Duration	Sample Size	Standard
Life Test	Life Test	Ta=25°C±5°C IF=20mA	1000hrs (hrs)	10PCS	
Environment Test	Thermal Shock	-10°C±5°C ←→ +100°C±5°C 5min. 10sec. 5min.	100cycles (cycles)	10PCS	
	Temperature C	-55°C±5°C ←→ +85°C±5°C 30min. 5min. 30min.	100cycles (cycles)	10PCS	
	High Temper. High Humidi	Ta=85°C±5% RH =85%±0.5 %RH	240hrs (hrs)	10PCS	
	High Temper. Storage	Ta=100°C±5%	1000hrs (hrs)	10PCS	
	Low Temper. Storage	Ta=-55°C±5%	1000hrs	10PCS	
Mechanical Test	Resistance to Soldering He	Ta=260°C±5%	5 sec.	10PCS	
	Lead Integrity	0.25 kg 0° ~ 90° ~ 0°	3 times	10PCS	




Hubei Kento Electronic Co., Ltd

5AY3UC09


Typical Optical/Electrical Characteristics Curves (Ta=25° Unless Otherwise Noted)



Current-Voltage Curve





Current-Luminous intensity Curve



Current-Luminous flux Curve

Hubei Kento Electronic Co., Ltd

5AY3UC09



Wavelengt

