

Current Transducer LTS 6-NP

$$I_{PN} = 2 - 3 - 6 A$$

For the electronic measurement of currents : DC, AC, pulsed, mixed, with a galvanic isolation between the primary circuit (high power) and the secondary circuit (electronic circuit).



Electrical data

I_{PN}	Primary nominal r.m.s. current	6	At
I_P	Primary current, measuring range	0 .. ± 19.2	At
\hat{I}_{PDC}	Overload capability	250	A
V_{OUT}	Analog output voltage @ I_P	$2.5 \pm (0.625 \cdot I_P / I_{PN})$	V
	$I_P = 0$	$2.5^{1)}$	V
N_S	Number of secondary turns (± 0.1 %)	2000	
R_L	Load resistance	≥ 2	k Ω
R_{IM}	Internal measuring resistance (± 0.5 %)	208.33	Ω
TCR_{IM}	Thermal drift of R_{IM}	< 50	ppm/K
V_C	Supply voltage (± 5 %)	5	V
I_C	Current consumption @ $V_C = 5$ V	Typ $28 + I_S^{(2)} + (V_{OUT} / R_L)$	mA
V_d	R.m.s. voltage for AC isolation test, 50/60 Hz, 1 mn	3	kV
V_e	R.m.s. voltage for partial discharge extinction @ 10 pC	> 1.5	kV
\hat{V}_w	Impulse withstand voltage 1.2/50 μ s	> 8	kV

Accuracy - Dynamic performance data

X	Accuracy @ $I_{PN}, T_A = 25^\circ C$	± 0.2	%
	Accuracy with R_{IM} @ $I_{PN}, T_A = 25^\circ C$	± 0.7	%
\mathcal{E}_L	Linearity error	< 0.1	%
TCV_{OUT}	Thermal drift of V_{OUT} @ $I_P = 0$	-10 $^\circ C$.. +85 $^\circ C$ -40 $^\circ C$.. -10 $^\circ C$	Typ 80 Max 200 ppm/K 250 ppm/K
TCE_G	Thermal drift of the gain	-40 $^\circ C$.. +85 $^\circ C$	50 ³⁾ ppm/K
V_{OM}	Residual voltage @ $I_P = 0$, after an overload of $3 \times I_{PN}$	$5 \times I_{PN}$ $10 \times I_{PN}$	± 0.5 mV ± 2.0 mV ± 2.0 mV
t_{ra}	Reaction time @ 10 % of I_{PN}	< 100	ns
t_r	Response time @ 90 % of I_{PN}	< 400	ns
di/dt	di/dt accurately followed	> 15	A/ μ s
f	Frequency bandwidth (0 .. -0.5 dB)	DC .. 100	kHz
	(-0.5 .. 1 dB)	DC .. 200	kHz

General data

T_A	Ambient operating temperature	-40 .. +85	$^\circ C$
T_S	Ambient storage temperature	-40 .. +100	$^\circ C$
	Insulating material group	III a	
m	Mass	10	g
	Standards ⁴⁾	EN 50178 (97.10.01) IEC 60950-1(01.10.26)	

Notes : ¹⁾ Absolute value @ $T_A = 25^\circ C$, $2.475 < V_{OUT} < 2.525$

²⁾ Please see the operation principle on the other side

³⁾ Only due to TCR_{IM}

⁴⁾ Specification according to IEC 61000-4-3 are not guaranteed between 95 and 110 MHz (value higher by 5% than the specification).

Features

- Closed loop (compensated) multi-range current transducer using the Hall effect
- Unipolar voltage supply
- Compact design for PCB mounting
- Insulated plastic case recognized according to UL 94-V0
- Incorporated measuring resistance
- Extended measuring range.

Advantages

- Excellent accuracy
- Very good linearity
- Very low temperature drift
- Optimized response time
- Wide frequency bandwidth
- No insertion losses
- High immunity to external interference
- Current overload capability.

Applications

- AC variable speed drives and servo motor drives
- Static converters for DC motor drives
- Battery supplied applications
- Uninterruptible Power Supplies (UPS)
- Switched Mode Power Supplies (SMPS)
- Power supplies for welding applications.

Copyright protected.

040318/12

