



COMPLEMENTARY SILICON POWER DARLINGTON TRANSISTORS

- SGS-THOMSON PREFERRED SALESTYPES

DESCRIPTION

The BDW91 is a silicon epitaxial-base NPN transistors in monolithic Darlington configuration mounted in Jedec TO-39 metal case, intended for use in linear and switching applications.

The complementary PNP types is BDW92.



ABSOLUTE MAXIMUM RATINGS

Symbol	Parameter	Value		Unit
		NPN	BDW91	
		PNP	BDW92	
V _{CBO}	Collector-Base Voltage ($I_E = 0$)		180	V
V _{CEO}	Collector-Emitter Voltage ($I_B = 0$)		180	V
V _{EBO}	Emitter-Base Voltage ($I_C = 0$)		6	V
I _C	Collector Current		4	A
I _B	Base Current		100	mA
P _{tot}	Total Dissipation at $T_{case} \leq 25^\circ\text{C}$ $T_{amb} \leq 25^\circ\text{C}$		10 1	W W
T _{stg}	Storage Temperature		-65 to 200	°C
T _j	Max. Operating Junction Temperature		200	°C

For PNP types voltage and current values are negative.

THERMAL DATA

R _{thj-case}	Thermal Resistance Junction-case	Max	17.5	°C/W
R _{thj-amb}	Thermal Resistance Junction-amb	Max	175	°C/W


ELECTRICAL CHARACTERISTICS ($T_{case} = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
I _{CBO}	Collector Cut-off Current ($I_E = 0$)	V _{CB} = 180 V			50	μA
I _{CEO}	Collector Cut-off Current ($I_B = 0$)	V _{CE} = 90 V			50	μA
I _{EBO}	Emitter Cut-off Current ($I_C = 0$)	V _{EB} = 6 V	0.4		2	mA
V _{CEO(sus)} *	Collector-Emitter Sustaining Voltage	I _C = 50 mA	180			V
V _{CE(sat)} *	Collector-Emitter Saturation Voltage	I _C = 2 A I _B = 4 mA			2	V
V _{BE} *	Base-Emitter Voltage	I _C = 2 A V _{CE} = 2 V			2.5	V
h _{FE} *	DC Current Gain	I _C = 2 A V _{CE} = 5 V I _C = 50 mA V _{CE} = 5 V	1000 150	3000 300		
V _F *	Parallel Diode Forward Voltage	I _F = 2 A			2.5	V
h _{fe}	Small Signal Current Gain	I _C = 0.5 A V _{CE} = .2 V f = 1 MHz		20		MHz

* Pulsed: Pulse duration = 300 μs, duty cycle 1.5 %
 For PNP types voltage and current values are negative.

TO39 MECHANICAL DATA

DIM.	mm			inch		
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.
A	12.7			0.500		
B			0.49			0.019
D			6.6			0.260
E			8.5			0.334
F			9.4			0.370
G	5.08			0.200		
H			1.2			0.047
I			0.9			0.035
L	45° (typ.)					



P008B

Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1996 SGS-THOMSON Microelectronics - Printed in Italy - All Rights Reserved

SGS-THOMSON Microelectronics GROUP OF COMPANIES

Australia - Brazil - Canada - China - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco - The Netherlands -
Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A