

HEX BUS DRIVERS WITH 3-STATE OUTPUTS

DESCRIPTION

The M74LS367AP is a semiconductor integrated circuit containing 6 buffers with 3-state output and is provided with output control inputs \overline{OC} and $\overline{2OC}$, which are common to 4 circuits and 2 circuits, respectively.

FEATURES

- Provided with output control inputs common to 4 circuits and 2 circuits.
- High fan-out
- High breakdown input voltage
- Wide operating temperature range ($T_a = -20 \sim +75^\circ C$)

APPLICATION

General purpose, for use in industrial and consumer equipment.

FUNCTIONAL DESCRIPTION

When \overline{OC} is low, high appears in the output Y if input A is high, and low appears if A is low. When \overline{OC} is high, Y is put in the high-impedance state irrespective of the status of A. For this reason, this device is most suitable for use as a bus line driver.


FUNCTION TABLE (Note 1)

\overline{OC}	A	Y
L	L	L
L	H	H
H	X	Z

Note 1: X : irrelevant


Z : high-impedance

PIN CONFIGURATION (TOP VIEW)



Outline 16P4

CIRCUIT SCHEMATIC (EACH BUFFER)



UNIT : Ω

HEX BUS DRIVERS WITH 3-STATE OUTPUTS**ABSOLUTE MAXIMUM RATINGS** ($T_a = -20 \sim +75^\circ\text{C}$, unless otherwise noted)

Symbol	Parameter	Conditions	Limits	Unit
V _{CC}	Supply voltage		-0.5 ~ +7	V
V _I	Input voltage		-0.5 ~ +15	V
V _O	Output voltage	Off-state	-0.5 ~ +5.5	V
T _{OPR}	Operating free-air ambient temperature range		-20 ~ +75	°C
T _{STG}	Storage temperature range		-65 ~ +150	°C

RECOMMENDED OPERATING CONDITIONS ($T_a = -20 \sim +75^\circ\text{C}$, unless otherwise noted)

Symbol	Parameter	Limits			Unit
		Min	Typ	Max	
V _{CC}	Supply voltage	4.75	5	5.25	V
I _{OH}	High-level output current	V _{OH} ≥ 2.4V	0	-2.6	mA
I _{OL}	Low-level output current	V _{OL} ≤ 0.4V	0	12	mA
		V _{OL} ≤ 0.5V	0	24	mA

ELECTRICAL CHARACTERISTICS ($T_a = -20 \sim +75^\circ\text{C}$, unless otherwise noted)

Symbol	Parameter	Test conditions		Limits			Unit
		Min	Typ*	Max	Min	Typ*	
V _{IH}	High-level input voltage			2			V
V _{IL}	Low-level input voltage					0.8	V
V _{IC}	Input clamp voltage	V _{CC} = 4.75V, I _{IC} = -18mA				-1.5	V
V _{OH}	High-level output voltage	V _{CC} = 4.75V, V _I = 0.8V V _I = 2V, I _{OH} = -2.6mA		2.4	3.1		V
V _{OL}	Low-level output voltage	V _{CC} = 4.75V	I _{OL} = 12mA		0.25	0.4	V
		V _I = 0.8V	I _{OL} = 24mA		0.35	0.5	V
I _{OZH}	Off-state high-level output current	V _{CC} = 5.25V, V _I (OC) = 2V, V _O = 2.4V				20	μA
I _{OZL}	Off-state low-level output current	V _{CC} = 5.25V, V _I (OC) = 2V, V _O = 0.4V				-20	μA
I _{IIH}	High-level input current	V _{CC} = 5.25V, V _I = 2.7V				20	μA
		V _{CC} = 5.25V, V _I = 10V				0.1	mA
I _{IL}	Low-level input current	OC	V _{CC} = 5.25V, V _I = 0.4V			-0.4	mA
		A	V _I (OC) = 0.4V V _I = 0.4V			-0.4	mA
			V _{CC} = 5.25V V _I (OC) = 2V V _I = 0.5V			-20	μA
I _{OS}	Short-circuit output current	V _{CC} = 5.25V, V _O = 0V		-40		-225	mA
I _{CC}	Supply current	V _{CC} = 5.25V, V _I = 0V, V _I (OC) = 4.5V			14	24	mA

* : All typical values are at $V_{CC} = 5V$, $T_a = 25^\circ\text{C}$.


Note 2: All measurements should be done quickly, and not more than one output should be shorted at a time.

SWITCHING CHARACTERISTICS ($V_{CC} = 5V$, $T_a = 25^\circ\text{C}$, unless otherwise noted)

Symbol	Parameter	Test conditions		Limits			Unit
		Min	Typ	Max	Min	Typ	
t _{PLH}	Low-to-high-level, high-to-low-level output propagation time, from input A to output Y	C _L = 45pF (Note 3)			7	16	ns
t _{PHL}					10	22	ns
t _{PZH}	Output enable time to high-level	R _L = 667Ω, C _L = 45pF (Note 3)			13	35	ns
t _{PZL}	Output enable time to low-level	R _L = 667Ω, C _L = 45pF (Note 3)			15	40	ns
t _{PHZ}	Output disable time from high-level	R _L = 667Ω, C _L = 5 pF (Note 3)			13	30	ns
t _{PLZ}	Output disable time from low-level	R _L = 667Ω, C _L = 5 pF (Note 3)			16	35	ns

HEX BUS DRIVERS WITH 3-STATE OUTPUTS




Note 3: Measurement circuit



Symbol	SW 1	SW 2
t_{PZH}	Open	Closed
t_{PZL}	Closed	Open
t_{PLZ}	Closed	Closed
t_{PHZ}	Closed	Closed

- (1) The pulse generator (PG) has the following characteristics:
 $PRR = 1\text{MHz}$, $t_r = 6\text{ns}$, $t_f = 6\text{ns}$, $t_w = 500\text{ns}$,
 $V_p = 3V_{p.p.}$, $Z_0 = 50\Omega$
- (2) All diodes are switching diodes ($t_{rr} \leq 4\text{ns}$)
- (3) C_L includes probe and jig capacitance.

TIMING DIAGRAM (Reference level = 1.3V)




MITSUBISHI LSTTLs
PACKAGE OUTLINES

MITSUBISHI {DGTL LOGIC} 07E D 6249827 0013561 3

T-90-20


TYPE 14P4 14-PIN MOLDED PLASTIC DIL

Dimension in mm



TYPE 16P4 16-PIN MOLDED PLASTIC DIL

Dimension in mm



TYPE 20P4 20-PIN MOLDED PLASTIC DIL

Dimension in mm

