



Frontier Electronics Corp.

667 E. COCHRAN STREET, SIMI VALLEY, CA 93065

TEL: (805) 522-9998 FAX: (805) 522-9989




E-mail: frontiersales@frontierusa.com

Web: <http://www.frontierusa.com>

10A DUAL SUPER FAST RECOVERY RECTIFIER

SFF100-005CT THRU SFF100-06CT

CASE : ITO-220AB(SFF100-XX) , FULLY INSULATED PACKAGE



	MILLIMETERS	
	MIN	MAX
B	9.72	10.27
C	6.30	6.90
D	14.50	15.50
E	13.00	13.80
F	-	4.1
G	2.41	2.67
H	-	1.52
I	-	0.9
J	-	4.8
K	-	3.1
L	2.5	2.9
M	-	0.8
O	-	Ø 3.4

FEATURES

- ULTRA FAST RECOVERY TIME
- LOW FORWARD VOLTAGE
- LOW THERMAL RESISTANCE
- HIGH CURRENT CAPABILITY
- HIGH VOLTAGE
- GLASS PASSIVATED CHIP JUNCTION
- LEAD FREE

MECHANICAL DATA

- CASE: TRANSFER MOLDED
- TERMINAL: MIL-STD-202F METHOD 208
- POLARITY: AS MARKED
- EPOXY: UL94V-0 FLAME RETARDANT MOLDING COMPOUND
- MOUNTING POSITION: ANY
- WEIGHT: 2.05 GRAMS

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS RATINGS AT 25°C AMBIENT TEMPERATURE UNLESS OTHERWISE SPECIFIED
SINGLE PHASE, HALF WAVE, 60 HZ, RESISTIVE OR INDUCTIVE LOAD. FOR CAPACITIVE LOAD, DERATE CURRENT BY 20%.

RATINGS	SYMBOL	SFF100 -005CT	SFF100 -01CT	SFF100 -015CT	SFF100 -02CT	SFF100 -03CT	SFF100 -04CT	SFF100 -05CT	SFF100 -06CT	UNITS
MAXIMUM RECURRENT PEAK REVERSE VOLTAGE	V _{RRM}	50	100	150	200	300	400	500	600	V
MAXIMUM RMS VOLTAGE	V _{RMS}	35	70	105	140	210	280	350	420	V
MAXIMUM DC BLOCKING VOLTAGE	V _{DC}	50	100	150	200	300	400	500	600	V
MAXIMUM AVERAGE FORWARD RECTIFIED CURRENT SEE FIG.1	I _O	10.0								A
PEAK FORWARD SURGE CURRENT, 8.3ms SINGLE HALF SINE-WAVE SUPERIMPOSED ON RATED LOAD	I _{FSM}	125								A
TYPICAL JUNCTION CAPACITANCE (NOTE 1)	C _J	60						85		PF
TYPICAL THERMAL RESISTANCE (NOTE 2)	R _{θjc}	2.2								°C/W
STORAGE TEMPERATURE RANGE	T _{STG}	- 55 TO + 150								°C
OPERATING TEMPERATURE RANGE	T _{OP}	- 55 TO + 150								°C


ELECTRICAL CHARACTERISTICS ($A_T T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)

CHARACTERISTICS	SYMBOL	SFF100-005CT	SFF100-01CT	SFF100-015CT	SFF100-02CT	SFF100-03CT	SFF100-04CT	SFF100-05CT	SFF100-06CT	UNITS	
MAXIMUM FORWARD VOLTAGE AT 5A PER LEG	V _F	1.3						1.70		V	
MAXIMUM DC REVERSE CURRENT AT TA=25°C	I _R	10									μA
MAXIMUM DC REVERSE CURRENT AT TA=100°C	I _R	100									μA
MAXIMUM REVERSE RECOVERY TIME (NOTE 3)	T _{RR}	35									nS

- NOTES: 1. MEASURED AT 1 MHZ AND APPLIED REVERSE VOLTAGE OF 4.0 VOLTS
2. THERMAL RESISTANCE JUNCTION TO CASE PER LEG MOUNTED ON HEAT SINK
3. REVERSE RECOVERY TEST CONDITIONS: $I_F = 0.5\text{A}$, $I_R = 1.0\text{A}$, $I_{RR} = 0.25\text{A}$

RATINGS AND CHARACTERISTIC CURVE SFF100-005CT THRU SFF100-06CT

FIG. 1 -TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC



NOTE: 1. RISE TIME=7ns MAX. INPUT IMPEDANCE=1 MOhms 22PF
2. RISE TIME =10 ns MAX. SOURCE IMPEDANCE=50 OHMS




FIG. 3 -TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS





FIG. 5 -TYPICAL JUNCTION CAPACITANCE

